

TABLE TOP CENTRIFUGE DSC-1512D

FEATURES:

- The Table Top Centrifuge will save space for the work desk.
- The outer shell of ABS can resist collisions.
- Without altering the rotor, it could accommodate 7ml, 10ml, and 15ml centrifuge tubes. (Optional attachments are 7ml tube adapters)
- With safety switch, the rotor will stop spinning when lid is lifted during operation
- This is a digital form that can easily set velocity and time. The RCF or RPM value can be seen on the LED display.
- The unit can be stopped easily with an automatic braking system.
- The method of auto-balancing can provide quiet and steady operation.

SPECIFICATIONS	
Speed	200~3400rpm
RCF	Digital display for time and speed value (or RCFvalue)
Timer	0~30 min. digital timer
Motor	Brushless DC
Rotor	AR-1512
Rotor Type	45° angle
Max. RCF	1,680g
Capacity	12x(1.5~15)ml
Standard Accessory	(10~15)ml tube adapter
Optional Accessory	(5~7) ml or (1.5~2.0) ml tube adapter
Weight (kg.)	N.W. 5.4 / G.W. 6.4
Overa ll Dimensions	W300xD300xH265mm
Power Supply	AC 100~240V 50/60Hz







Rotor AR-1524

TUBE ADAPTOR:



Model	Speed (RPM)	Туре	Max. RCF (g)	Capacity	Standard Accessory
AR-1512	200-3400	45° ang l e	1,066	12x (10~15) ml	10~15ml tube adapter



