



LOW SPEED CENTRIFUGE DM0506

DLAB DM0506 low-speed centrifuge, supplied with built-in fixed angle rotor A6-15P which can hold up to 15mL/10mL/7mL/5mL×6 tubes. It is widely used for blood or urine separation in medical routine practice in hospitals, clinics or research institutes.

FEATURES:

- Speed range from 300-5000rpm
- Rotor speed can be set and displayed by RPM or G-force
- Defined program by knob will be stored and activated when power on
- Two programs P1/P2, easy to start the procedure by one key
- Two deceleration speeds setting to meet different requirements
- Easy-to-read processing display and sound alert
- Automatic lid-lock release after running
- Maintenance-free brushless DC motor



SPECIFICATIONS

| | |
|---------------------------|--|
| Speed Range | 300-5000rpm, increment:10rpm |
| Max. RCF | 2350xg, increment: 10g |
| Speed Accuracy | ±20rpm |
| Rotor Capacity | 6x15mL / 10mL / 7mL / 1.5-5ml |
| Run Time | 30sec-99min, HD(continuous running) |
| Display | LCD |
| Programs Memory | 2 |
| Acceleration/Deceleration | 1↑ 2↓ |
| Safety Devices | Door interlock, Overspeed detector, Automatic internal diagnosis |
| Motor | Brushless DC motor |
| Power | Single-phase, 100V-240V,50Hz/60Hz, 70W |
| Dimension(WxDxH) | 300 x 240 x 180mm |
| Weight | 5.2kg |
| Advanced Features | Speed/RCF switch; sound-alert function |

ADAPTORS:



A5P17
5ml adapter,
Adapted to 13×75mm
blood collection tube



A2P17
1.5/2ml Cryogenic Vials/
centrifuge tube adapter



TruLaboratories
Corporation

+632 82-TRULAB (878522)
+63917.878.2288 • +63925.878.2288
www.trulaboratories.com