



PCR CENTRIFUGE

D1008 Series

FEATURES:

- Ideal for microfiltration and quick spin-downs
- Easy-to-use with dual start/stop function
- 7000rpm fixed speed (D1008)
- Compatible with 2mL x 8 and PCR 8 x 2 rotors
- Quiet running, noise level ≤ 45 dB
- Rotor change without tools
- Accelerates and brakes in seconds



Quiet Operation



Vibration Free

SPECIFICATIONS

Max. Speed	7000rpm
Max. RCF	2680 x g
Rotor Capacity	0.2/0.5/1.5/2.0mLx8; 0.2mLx16 PCR strips or 0.2mLx2 PCR 8 strips
Run Time	Continuous operation
Driving Motor	DC motor
Power	AC 220V/50Hz/60Hz 20W
Noise Level	≤ 45 dB
Dimesions (DxWxH)	160 x 170 x 122mm
Weight	0.5kg
Advanced Features	CE cTÜVus FCC MCA

ROTORS:

A08-2

Max. Speed: 10000/7000/5000rpm
 Max. RCF: 5460/2680/1360xg
 Rotor Capacity: 2mL/1.5mLx8, 0.2mLx8, 0.5mLx8
 Rotor Material: High strength plastic



A02-PCR8

Max. Speed: 10000/7000/5000rpm
 Max. RCF: 5460/2680/1360xg
 Rotor Capacity: 0.2mLx16 PCR strips, 0.2 mLx2 PCR 8 strips
 Rotor Material: High strength plastic



ADAPTORS

SA02P2

0.2mL rotor adaptor
 Used with A08-2 rotor
 8pcs/pk



SA05P2

0.5mL rotor adaptor
 Used with A08-2 rotor
 8pcs/pk

